

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



## FIG. 7






FIG. 8




# FIG. 9




**FIG. 10**

10/17



## FIG. 11



## FIG. 12






FIG. 13



**FIG. 14**



## FIG. 15





FIG. 16



## FIG. 17

150  
SHADING  
DATA FILE

151

152

VENDOR NAME : XXXX  
 PRODUCT NAME : YYYYY  
 SERIAL NUMBER : PXY00012467  
 DRIVER VERSION : ver5.3  
 SCAN COUNT : 35

153

FIRST MODE : COLOR, 75DPI, 800 ns,  
 REFLECTING  
 RECORD START=400, RECORD  
 LENGTH=11600

SECOND MODE : COLOR, 150DPI, 1000 ns,  
 REFLECTING  
 RECORD START=400, RECORD  
 LENGTH=0

154

THIRD MODE : COLOR, 300DPI, 2000 ns,  
 REFLECTING  
 RECORD START=12000, RECORD  
 LENGTH=46400

•

•

•

155

N-TH MODE : GRAY, 600DPI, 900 ns,  
 REFLECTING  
 RECORD START=58400, RECORD  
 LENGTH=46400

400TH BYTE

156

CALIBRATION DATA OF FIRST MODE  
 SHADING DATA OF FIRST MODE

157

SHADING DATA OF THIRD MODE

158

CALIBRATION DATA OF N-TH MODE  
 SHADING DATA OF N-TH MODE